

TECHNICAL DATA SHEET SOLENOX 3427

SOLENOX 3427 is an antioxidant. It can be used as an additive to improve the fuel stability and overall blending capabilities of light and middle distillates.

Key Benefits

- Effective polymerization inhibitor
- Retards gum formation
- Prolongs storage life of fuels
- Allows for more efficient fuel combustion
- Increases refiners' blending processability

Typical Characteristics

Parameter	Specification
Appearance	Colourless to yellow liquid
Specific gravity	0.90 – 1.00
Flash point (°C)	≥ 90
Viscosity @ 40°C (cSt)	6 – 10

Recommended Dosage

Actual dosage will largely depend on the end application, fuel specifications and base oil properties.

Packaging and Storage

SOLENOX 3427 is packaged in 55 USG drum.

Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking. Avoid using rubber (natural or synthetic) as packaging materials.

Recommended Handling

All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Safety Data Sheet (SDS).

This document is supplied solely for informational purposes and Solent Chemicals makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.