

TECHNICAL DATA SHEET

SOLASCAV T

SOLASCAV T is a filming additive designed to inhibit corrosion of non-ferrous metals caused by sulfur-containing corrodents, such as hydrogen sulfide, mercaptans and elemental sulfur.

Key Benefits

- Protects copper and silver components in vehicle and distribution systems against attack by active sulfur and sulfur compounds
- Reduces vehicle fuel system failures
- Good low-temperature handling properties minimizes the need for dilution or heated storage

Typical Characteristics

Parameter	Specification
Appearance	Liquid
Density (g/cm ³)	1.04
Flash point (°C)	173
Acid number (mg KOH/g)	8

Recommended Dosage

2 – 20 ppm. Actual dosage will largely depend on the end application, fuel specifications and type of sulfur species present.

Packaging and Storage

SOLASCAV T is packaged in 55 USG drum.

Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking. Avoid using rubber (natural or synthetic) as packaging materials.

Recommended Handling

All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Safety Data Sheet (SDS).

This document is supplied solely for informational purposes and Solent Chemicals makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.