

SOL-LUBE E is a neutral ester-based lubricity additive specially designed for the treatment of a wide range of middle distillates, including ultra-low sulfur diesel (ULSD).

Key Benefits

- Improves lubricity of diesel fuels
- Reduces wear on the fuel injection equipment, prolonging engine durability
- Keeps the injector clean and prevents the fuel tank and lines from corrosion

Typical Characteristics

Parameter	Specification
Appearance	Liquid
Specific gravity @ 15°C (g/cm ³)	0.95
Flash point (°C)	> 100
Pour point (°C)	< -6
Viscosity @ 40°C (mm ² /s)	65

Recommended Dosage

Actual dosage will largely depend on the end application, fuel specifications and base oil properties.

Packaging and Storage

SOL-LUBE E is packaged in 55 USG drum.

Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking. Avoid using rubber (natural or synthetic) as packaging materials.

Recommended Handling

All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Safety Data Sheet (SDS).

This document is supplied solely for informational purposes and Solent Chemicals makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.