

TECHNICAL DATA SHEET EP LUB

EP LUB is a highly effective lubricant for various drilling fluid systems. It can effectively reduce the friction coefficient of the drilling tool and the torque force of the plate. It can also prevent the drilling fluid from sticking. EP LUB is stable, convenient, eco-friendly and harmless to human body.

Typical Characteristics

Parameter	Specification
Appearance	Dark brown or black liquid
Density @ 20°C (g/mL)	0.89 – 0.98
Water solubility	Dispersible in water
Flash point, closed cup (°C)	> 100

Application

- Especially used in horizontal wells and highly deviated wells
- Reduces the flow resistance of the drilling fluid and the friction coefficient of filter cake, reduces TOB and increases HHP to prevent sticking
- Completely water-dispersible, making them good for reducing friction coefficient and torque in a variety of water-based drilling fluid systems (i.e. freshwater, seawater and saltwater systems)
- Effectively overcomes the insufficient lubricity of ordinary lubricants - under high load conditions, it has better extreme pressure and anti-wear effect, which can form a stronger extreme pressure lubricating film on the surface of metal drilling tools to protect the drilling tool, extend the life of the drill bit, reduce the torque of the drill rods, increase the drilling speed and reduce the possibility of differential sticking
- Reduces the wear on drill pipe and drill collar, especially in irregular caliper and deviated wells and directional wells, greatly improving drilling efficiency

Packaging and Storage

EP LUB is packaged in 180 kg drum or 900 kg drum.

Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

Recommended Handling

All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Safety Data Sheet (SDS).

This document is supplied solely for informational purposes and Solent Chemicals makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.