

# TECHNICAL DATA SHEET NWOSOL 15

NWOSOL 15 is a safe and eco-friendly nano-washing solvent. It has high oil-washing efficiency, particularly suitable for removing dense oil layers.

## **Typical Characteristics**

Parameter	Specification
Appearance	Colourless to yellow liquid
Specific gravity (g/cm <sup>3</sup> )	0.85 – 1.05
Surface tension (mN/m)	≤ 32
Oil washing rate (%)	≥ 30

#### **Application**

- Reduces the critical micelle concentration (CMC), making it easier to form micelles and microemulsions in the washing solvent
- Facilitates miscibility with the oil phase, increasing the flowability of the remaining oil
- Effectively reduces interfacial tension between injected water and crude oil
- Enhances emulsifying, penetrating and peeling ability
- Increases the sweep efficiency of subsequent liquid

# **Packaging and Storage**

NWOSOL 15 is packaged in 180 kg drum or 900 kg drum.

Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

### **Recommended Handling**

All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Safety Data Sheet (SDS).

This document is supplied solely for informational purposes and Solent Chemicals makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.